


Technical sheet :

# 160 ATJ E

OXYGEN



 **MANITOU**  
HANDLING YOUR WORLD


| Capacities                                         |         | Metric                                                                              |
|----------------------------------------------------|---------|-------------------------------------------------------------------------------------|
| Working height                                     | h21     | 16.03 m                                                                             |
| Platform height                                    | h7      | 14.05 m                                                                             |
| Max. outreach                                      |         | 8.11 m                                                                              |
| Overhang                                           |         | 7.43 m                                                                              |
| Pendular arm rotation (left / right)               |         | 90 ° / 90 °                                                                         |
| Pendular arm rotation (top / bottom)               |         | +65 ° / -59.50 °                                                                    |
| Platform capacity                                  | Q       | 250 kg                                                                              |
| Turret rotation                                    |         | 350 °                                                                               |
| Platform rotation (right / left)                   |         | 90 ° / 90 °                                                                         |
| Number of people (indoor / outdoor)                |         | 2 / 2                                                                               |
| Weight and dimensions                              |         |                                                                                     |
| Platform weight*                                   |         | 6784 kg                                                                             |
| Platform dimensions (length x width)               | lp / ep | 1.80 m x 0.76 m                                                                     |
| Floor height (access)                              | h20     | 0.46 m                                                                              |
| Overall length                                     | l1      | 6.50 m                                                                              |
| Overall width                                      | b1      | 2.32 m                                                                              |
| Overall height                                     | h17     | 2.39 m                                                                              |
| Overall length (stowed)                            | l9      | 4.48 m                                                                              |
| Overall height (stowed)                            | h18 *** | 2.77 m                                                                              |
| Counterweight offset (turret at 90°)               | a7      | 0.85 m                                                                              |
| Counterweight Oversize / Reach                     |         | 0.26 m                                                                              |
| External turning radius                            | Wa3     | 3.75 m                                                                              |
| Ground clearance at centre of wheelbase            | m2      | 0.35 m                                                                              |
| Wheelbase                                          | y       | 2.30 m                                                                              |
| Performances                                       |         |                                                                                     |
| Drive speed - stowed                               |         | 5.20 km/h                                                                           |
| Drive speed - raised                               |         | 0.70 km/h                                                                           |
| Gradeability                                       |         | 45 %                                                                                |
| Permissible leveling                               |         | 5 °                                                                                 |
| Wheels                                             |         |                                                                                     |
| Tires type                                         |         | Foam Filled Non Marking                                                             |
| Standard tires                                     |         | 840 x 295 mm / 33x12 D610                                                           |
| Drive wheels (front / rear)                        |         | 2 / 2                                                                               |
| Steering wheels (front / rear)                     |         | 2 / 2                                                                               |
| Braking wheels (front / rear)                      |         | 0 / 2                                                                               |
| Engine/Battery                                     |         |                                                                                     |
| Battery voltage                                    |         | 48 V                                                                                |
| Battery nominal voltage / capacity                 |         | 48 V / 480 Ah                                                                       |
| Battery energy                                     |         | 23 kWh                                                                              |
| On-board charger (V / A)                           |         | 48 V / 60 A                                                                         |
| Miscellaneous                                      |         |                                                                                     |
| Number of cycles with STD Battery (HIRD)           |         | 58                                                                                  |
| Ground Pressure                                    |         | 13 daN/cm2                                                                          |
| Hydraulic Pressure                                 |         | 250 bar                                                                             |
| Hydraulic tank capacity                            |         | 24 l                                                                                |
| Sound pressure level (platform work station) (LpA) |         | 70 dB                                                                               |
| Vibration on hands/arms                            |         | < 2.50 m/s²                                                                         |
| Standards compliance                               |         |                                                                                     |
| This machine is in compliance with:                |         | European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) |

\*Varies according to options and standards of the country to which the machine is delivered




\*\* According to "REDUCE cycle"

160 ATJ e - Load chart

Load Chart for MEWP Metric



160 ATJ e - Dimensional drawing



# Equipment

| Standard                                                                     |
|------------------------------------------------------------------------------|
| 220V predisposition in the platform                                          |
| 4 simultaneous movements                                                     |
| 4 wheel drive                                                                |
| 4 wheel steer with crab mode                                                 |
| Additional foot-operated horn                                                |
| Audible alarm and illuminated indicator lamp (leveling, overload, lowering)  |
| Backup electrical pump                                                       |
| Battery reserve mode                                                         |
| CAN bus technology                                                           |
| Differential locking on rear axle                                            |
| Driver presence pedal                                                        |
| Easy Link with 2 year Service                                                |
| Easy Manager                                                                 |
| Emergency stop button in platform and on frame                               |
| Front axle with limited slip                                                 |
| Fully galvanized basket with removable floor - Width: 2100 mm (6 ft. 11 in.) |
| Galvanized basket - Width: 1800 mm (5 ft. 11 in.)                            |
| Hour meter                                                                   |
| LED rotating beacon                                                          |
| Large color screen on turret                                                 |
| Leveling unlocking                                                           |
| Load sensing pump                                                            |
| Oscillating front axle                                                       |
| Screen information in the basket                                             |
| Simplified lifting system without spreader bar                               |
| Simultaneous steering and turret rotation functions                          |
| Slinging and securing rings                                                  |

| Optional                                                                                     |
|----------------------------------------------------------------------------------------------|
| 109 V electric plug 16A                                                                      |
| Antitheft digicode                                                                           |
| Audio warning on all motion                                                                  |
| Audio warning on all motion                                                                  |
| Audio warning on all motion - White noise                                                    |
| Audio warning on translation - White noise                                                   |
| Biodegradable hydraulic oil - Grade 32                                                       |
| Compressed air pipe pre-fitting                                                              |
| Continuous turret rotation                                                                   |
| Earthing and short-circuiting pre-fitting (Bolted ball)                                      |
| Easy Link - With access control keypad                                                       |
| Easy Link - With remote lock                                                                 |
| Electric central filling system                                                              |
| Electric plug - 230V - In the basket - With differential circuit breaker - Europe (E/F) type |
| Foam-filled tires 914 x 381 mm / 36X15D609                                                   |
| Front metallic wheels + Rear metallic wheels                                                 |
| Galvanized basket - Width: 1800 mm (5 ft. 11 in.) + Side swing gate                          |
| Galvanized basket - Width: 2100 mm (6 ft. 11 in.)                                            |
| Galvanized basket - Width: 2100 mm (6 ft. 11 in.) + Side swing gate                          |
| Hydraulic oil pre-heater                                                                     |
| Key lock on turret cover                                                                     |
| Key lock on turret cover                                                                     |
| LED work light - On basket                                                                   |
| Lighting pack                                                                                |
| Lower control box protection                                                                 |
| Non-marking Foam Inflated Tires 914 x 381 mm / 36x15D609                                     |
| OSS - Operation Safety System                                                                |
| Personalized paintwork                                                                       |
| Rail protection                                                                              |
| Safety kit - Helmet and harness                                                              |
| Setting to block the telescope                                                               |
| Two safety kits (helmet + harness)                                                           |
| Water pre-fitting                                                                            |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes